



HAVELLS

Powering Lives...

ENTERPRISE SOLUTIONS

LV SWITCHGEAR & POWER QUALITY

Pricelist w.e.f. 11th March, 2025

ABOUT US

Redefining the modern homes with innovation and excellence

Havells is at the forefront of transforming modern living spaces by offering innovative solutions that elevate everyday experiences. With a deep understanding of consumer needs, the company has expanded its footprint across every aspect of home life, creating environment that are not only functional but also comfortable, stylish, and future-ready. To make these solutions accessible, Havells leverages an extensive distribution network encompassing 18,000 dealers, over 1,000 exclusive brand stores, intensifying presence in modern retail, e-commerce and quick commerce.

The company's portfolio includes power brands like Havells, Havells Crabtree, Lloyd, REO, Havells Studio, and Standard each designed to cater to the unique demands of today's consumers.

Anchored in the 'Make in India' initiative, Havells operates 16 cutting-edge manufacturing facilities across India, producing 90% of its products in-house. At the forefront of Havells product evolution lies its Customer Experience & Designs (CXD) Studio, where creativity and user-centric design converge. This is complemented by its Centre for Research & Innovation (CRI), supported by four advanced R&D centres, enabling Havells to consistently deliver products that are both functional and visually compelling.

Driven by a commitment to innovation, quality, and design, the company also upholds sustainable practices throughout its operations, including eco-friendly manufacturing processes and energy-efficient product design, contributing to a greener and more sustainable future.



CORPORATE OFFICE, NOIDA



State-of-the-Art Manufacturing Unit



Industry 4.0 Process



Center For Research & Innovation



Customer Experience & Design

16 Manufacturing Units

~18000 Strong Dealer Network

4 Research Centres

48 Offices

DRIVEN BY INNOVATION. POWERED BY INDIA.



Innovation



Technology



Digitalization



Industrial Motor Starter - HGS



HGS - Trusted Global Range

Motor Starters

Motor Control Solutions for higher Safety, Reliability & Performance



DOL Starters
Ratings - 0.55 kW to 37 kW
(0.75 HP to 50 HP)



ASD Starters
Ratings - 7.5 kW to 110 kW
(10 HP to 150 HP)



ASD 3 ϕ Submersible Starters
Ratings - 22 kW to 37 kW
(30 HP to 50 HP)



ASD 3 ϕ Submersible Starters DLX
(with Short-circuit Protection)
Ratings - 22 kW to 37 kW
(30 HP to 50 HP)

Industrial Motor Starter - HGS

Direct Online Starter - HGS Series



Features:

- Range : 0.55 kW to 37 kW (0.75 HP to 50 HP)
- Conforms to IS/IEC 60947-4-1
- Provided with Protection Degree IP 54
- Extended wide band coil
- FRLS (Fire retardant low smoke) Internal wiring
- Starter Type - Air Break
- Class H Insulation

HSN Code: 85369010

HP	kW	Contactor Rating	Overload Relay Range (A)	Item Code	Per Unit LP (₹)
0.75 HP ▲	0.55 kW	12 A	1.5 A - 2.1 A	IHHDOLFAWE	3695.00
1 HP	0.75 kW	12 A	2 A - 3 A	IHHDOLGAWE	
2 HP ▲	1.5 kW	12 A	2.8 A - 4.2 A	IHHDOLHAWWE	
3 HP ▲	2.2 kW	12 A	4.0 A - 6.0 A	IHHDOLJAWWE	
5 HP ▲	3.7 kW	12 A	6 A - 9 A	IHHDOLLAWE	
7.5 HP ▲	5.5 kW	18 A	12 A - 18 A	IHHDOLMAWE	4435.00
10 HP ▲	7.5 kW	22 A	12 A - 18 A	IHHDOLNAWE	
15 HP ▲	11 kW	32 A	17 A - 25 A	IHHDOLPBWE	
20 HP	15 kW	32 A	22 A - 32 A	IHHDOLWBW	
25 HP	18.5 kW	40 A	28 A - 40 A	IHHDOLXBW	
30 HP	22 kW	50 A	34 A - 50 A	IHHDOLYCW	18080.00
40 HP	30 kW	65 A	45 A - 65 A	IHHDOL1CW	22330.00
50 HP	37 kW	85 A	59 A - 85 A	IHHDOL3DW	25890.00

Fully Automatic Star-Delta Starter (ASD) - HGS Series



Features:

- Range : 7.5 kW to 110 kW (10 HP to 150 HP)
- Conforms to IS/IEC 60947-4-1
- Provided with Protection Degree IP 54
- Extended wide band coil
- FRLS (Fire retardant low smoke) Internal wiring
- Starter Type - Air Break
- Class H Insulation

HSN Code: 85369010

HP	kW	Contactor Size	Overload Relay Range (A)	Item Code	Per Unit LP (₹)
5 HP	3.7 kW	12 A	4.0 A - 6 A	IHHASDMAW	14025.00
7.5 HP	5.5 kW	18 A	6.0 A - 9 A	IHHASDPAW	14025.00
10 HP ▲	7.5 kW	18 A	8.0 A - 12 A	IHHASDRAW	14025.00
12.5 HP	9.3 kW	18 A	8.0 A - 12 A	IHHASDTAW	14220.00
15 HP ▲	11 kW	22 A	12 A - 18.0 A	IHHASDTBW	14280.00
20 HP ▲	15 kW	25 A	15 A - 22 A	IHHASDUBW	16070.00
25 HP ▲	18.5 kW	32 A	17 A - 25 A	IHHASDVBW	18090.00
30 HP ▲	22 kW	32 A	22 A - 32 A	IHHASDWBW	19735.00
35 HP	26 kW	32 A	28 A - 40 A	IHHASDXBW	29295.00
40 HP	30 kW	50 A	28 A - 40 A	IHHASDXCW	40500.00
50 HP	37 kW	50 A	34 A - 50 A	IHHASDYCW	50015.00
60 HP	45 kW	50 A	45 A - 65 A	IHHASD1CWA	73395.00
75 HP	55 kW	65 A	45 A - 65 A	IHHASD1CWB	80735.00
90 HP	67.5 kW	85 A	59 A - 85 A	IHHASD3DW	94495.00
100 HP	75 kW	100 A	70 A - 100 A	IHHASD4DW	99145.00
125 HP	90 kW	115 A	78 A - 130 A	IHHASD7EW	136580.00
150 HP	110 kW	150 A	90 A - 150 A	IHHASD8EW	138545.00

▲ Stockable Item

For details on technical parameters & non stockable items contact nearest sales office.

Automatic Star Delta Submersible Starter (STD) - HGS Series

Features:

- Range : 22 kW to 37 kW (30 HP to 50 HP)
- Conforms to IS/IEC 60947-4-1
- Provided with Protection Degree IP 54
- Extended wide band coil
- FRLS (Fire retardant low smoke) Internal wiring
- In-built metering
- Class H Insulation



HSN Code: 85369010

HP	kW	Full load Line Current	Full Load phase current	Contactor Size	Overload Relay Range (A)	Item Code	Per Unit LP (₹)
30 HP	22 kW	43.5 A	25.12 A	50 A	28 A - 40 A	IHHSSDXCW	40870.00
35 HP	26 kW	50.75 A	29.30 A	50 A	34 A - 50 A	IHHSSDYCWA	43310.00
40 HP	30 kW	58 A	33.49 A	65 A	34 A - 50 A	IHHSSDYCWB	47635.00
45 HP	33.6 kW	65.25 A	37.67 A	75 A	45 A - 65 A	IHHSD1DW	59545.00
50 HP	37 kW	72.5 A	41.86 A	85 A	52 A - 75 A	IHHSD2DW	64950.00

Automatic Star Delta Submersible Starter DLX (with short-circuit Protection) - HGS Series

Features:

- Range : 22 kW to 37 kW (30 HP to 50 HP)
- Conforms to IS/IEC 60947-4-1
- Provided with Protection Degree IP 54
- Extended wide band coil
- FRLS (Fire retardant low smoke) Internal wiring
- In-built metering & MCB
- Class H Insulation



HSN Code: 85369010

HP	kW	Full load Line Current	Full Load phase current	Contactor Size	Overload Relay Range (A)	TP MCB Rating (A)	Item Code	Per Unit LP (₹)
30 HP	22 kW	43.5 A	25.12 A	50 A	28 A - 40 A	100 A	IHHDSDXCW	42045.00
35 HP	26 kW	50.75 A	29.30 A	50 A	34 A - 50 A	100 A	IHHSDSYCWA	44530.00
40 HP	30 kW	58 A	33.49 A	65 A	34 A - 50 A	100 A	IHHSDSYCWB	48935.00
45 HP	33.6 kW	65.25 A	37.67 A	75 A	45 A - 65 A	125 A	IHHSD1DW	61075.00
50 HP	37 kW	72.5 A	41.86 A	85 A	52 A - 75 A	125 A	IHHSD2DW	66585.00

▲ Stockable Item

For details on technical parameters & non stockable items contact nearest sales office.

Effective from 11th March, 2025

List Price (LP) are in Indian ₹ & as per Standard Terms & Conditions **HAVELLS 71**

Spares for Industrial Motor Starter - HGS Series



HSN Code: 85389000

Type	Item Code	Per Unit LP (₹)
Start Push Button - Green	ICELL00002	220.00
Stop Push Button - Red	ICELL00003	
Motor ON Indicating Light-Green	ICELKL00015	355.00
Motor Trip Indicating Light-Yellow	ICELKL00013	
SPP	ISCELXL00063	3710.00
Combined Voltmeter & Ammeter	ISCEMLX0007	1450.00
Terminal Block 6 way	ICELPSMX001	545.00
Terminal Block 3 way	ICELPSMX002	330.00
VOLT.SEL SW. C/G	ICELQL00021	505.00
Star Delta Timer	ICELRPSL005	3195.00
Mini Rocker Switch - SPP By Pass	ISCELEL00218	55.00



▲ Stockable Item

For details on technical parameters & non stockable items contact nearest sales office.

Agricultural Motor Starter



Agricultural Motor Starter



3 ϕ Urja Lite DOL Starters
Ratings - 0.19 kW to 7.5 kW
(0.25 HP to 10 HP)



1 ϕ & 3 ϕ Urja DOL Starters
Ratings - 0.55 kW to 11 kW
(0.75 HP to 15 HP) - 3 ϕ
Ratings - 0.37 kW to 2.2 kW
(0.5 HP to 3 HP) - 1 ϕ



3 ϕ DOL Starter Submersible
Pump Controller
Ratings - 0.75 kW to 11 kW
(1 HP to 15 HP)



3 ϕ ASD Submersible
Pump Controller
Ratings - 3.7 kW to 15 kW
(5 HP to 20 HP)



1 ϕ Submersible Starters with Start
& Run Capacitor (Powerguard)
Ratings - 0.37 kW to 2.2 kW
(0.5 HP to 3 HP)



1 ϕ Submersible Pump Controller
(Powerguard)
Ratings - 0.37 kW to 2.2 kW
(0.5 HP to 3 HP)

Motor Starter

urja Urja Lite DOL Starters

Features:

- Range: upto 10 HP DOL
- Wide Band Coil 380 V (250 V - 440 V)
- Enclosure Dust, Vermin & Moisture Proof
- Quick Fit Technology
- Hight Electrical & Mechanical Life



HSN Code: 85369010

HP	kW	Contactor	O/L Relay	Motor Starter	
		(A)	(A)	Item Code	Per Unit LP (₹)
0.25 HP	0.19 kW	12 A	0.6 A - 1 A	IHADOB1LH	3075.00
0.5 HP	0.37 kW	12 A	1 A - 1.6 A	IHADOB1LH	3075.00
1 HP	0.75 kW	12 A	1.5 A - 2.5 A	IHADOB1LH	3075.00
2 HP ▲	1.5 kW	12 A	2.5 A - 4 A	IHADOB1LH	3075.00
3 HP ▲	2.2 kW	12 A	4 A - 6.5 A	IHADOB1LH	3075.00
5 HP ▲	3.7 kW	12 A	6 A - 10 A	IHADOB1LH	3075.00
7.5 HP ▲	5.6 kW	16 A	9 A - 14 A	IHADOB1LH	3075.00
10 HP ▲	7.5 kW	25 A	13 A - 21 A	IHADOB1LH	3675.00

urja DOL Starters 3 Phase - Agri Series

Features:

- Range : 0.55 kW to 11 kW (0.75 HP to 15 HP)
- Conforms to IS/IEC 60947-4-1
- Provided with Protection Degree IP 54
- Extended wide band coil
- FRLS (Fire retardant low smoke) Internal wiring
- Starter Type - Air Break
- Class H Insulation



Direct Online Starter - (Ideal for Agri Pump Application)

HSN Code: 85369010

HP	kW	Contactor	O/L Relay	Motor Starter	
		(A)	(A)	Item Code	Per Unit LP (₹)
0.75 HP	0.55 kW	16 A	1.07 A - 1.7 A	IHADOA1K	3500.00
1 HP ▲	0.75 kW	16 A	1.58 A - 2.5 A	IHADOA1K	
2 HP ▲	1.5 kW	16 A	2.4 A - 3.8 A	IHADOA1K	
3 HP ▲	2.2 kW	16 A	3.8 A - 6.0 A	IHADOA1K	
5 HP ▲	3.7 kW	16 A	6.0 A - 9.3 A	IHADOA1K	
7.5 HP ▲	5.5 kW	20 A ▲	8.9 A - 13.5 A	IHADOA1K	3850.00
		20 A	13.2 A - 20 A	IHADOA1KA	
		20 A	17.4 A - 24 A	IHADOA1KB	
10 HP ▲	7.5 kW	20 A	13.2 A - 20 A	IHADOA1K	4945.00
15 HP ▲	11 kW	25 A	17.4 A - 24 A	IHADOA1K	

urja DOL Starters Single Phase - Agri Series

Features:

- Range : 0.37 kW to 2.2 kW (0.5 HP to 3 HP)
- Conforms to IS/IEC 60947-4-1
- Provided with Protection Degree IP 54
- Extended wide band coil
- FRLS (Fire retardant low smoke) Internal wiring
- Starter type Air break
- Class H Insulation



Direct Online Starter Single Phase

HSN Code: 85369010

HP	kW	FLC (A)	Contactor (A)	O/L Relay (A)	Item Code	Per Unit LP (₹)
0.5 HP	0.37 kW	3.12 A	20 A	3.8 A - 6.0 A	IHUDOLG1F1	2275.00
1 HP ▲	0.75 kW	6.24 A	20 A	6 A - 9.3 A	IHUDOLH1F1	
1.5 HP ▲	1.1 kW	9.15 A	20 A	8.9 A - 13.5 A	IHUDOLK1F1	
2 HP ▲	1.5 kW	12.47 A	20 A	13.2 A - 20 A	IHUDOLK1FA	2335.00
3 HP ▲	2.2 kW	18.71 A	25 A	17.4 A - 24 A	IHUDOLL1F1	

▲ Stockable Item

For details on technical parameters & non stockable items contact nearest sales office.

urja Direct Online Starter Submersible Pump Controller (Standard)

3 Phase - Agri Series

Features:

- Range : 0.75 kW to 11 kW (1 HP to 15 HP)
- Conforms to IS/IEC 60947-4-1
- Provided with Protection Degree IP 54
- SPP with auto manual switch
- FRLS (Fire retardant low smoke) Internal wiring
- Combined V / A meter, Voltmeter selector switch
- ON OFF indication



HSN Code: 85369010

HP	kW	Max. Operational Current (A)	Contactor AC3 (A)	OLR (A)	Item Code	Per Unit LP (₹)
1 HP	0.75 kW	1.90 A	20 A	1.58 A - 2.5 A	IHSDOAF1KA	10375.00
2 HP	1.5 kW	3.81 A	20 A	3.8 A - 6.0 A	IHSDOAH1KA	
3 HP ▲	2.2 kW	5.71 A	20 A	3.8 A - 6.0 A	IHSDOAH1KB	
5 HP ▲	3.7 kW	9.52 A	20 A	8.9 A - 13.5 A	IHSDOAK1KA	
7.5 HP ▲	5.5 kW	14.27 A	20 A	13.2 A - 20 A	IHSDOAL1KA	
10 HP ▲	7.5 kW	19.03 A	25 A	13.2 A - 20 A	IHSDOAL1KB	10915.00
12.5 HP	9.3 kW	23.79 A	32 A	17.4 A - 24 A	IHSDOAM1KA	11460.00
15 HP	11 kW	28.55 A	32 A	22 A - 30 A	IHSDOAN1KA	12725.00

urja Automatic Star Delta Submersible Pump Controller (Standard)

3 Phase - Agri Series

Features:

- Range : 0.75 kW to 11 kW (1 HP to 15 HP)
- Conforms to IS/IEC 60947-4-1
- Provided with Protection Degree IP 54
- SPP with auto manual switch
- FRLS (Fire retardant low smoke) Internal wiring
- Combined V / A meter, Voltmeter selector switch
- ON OFF indication
- Star Delta Timer



HSN Code: 85369010

HP	Max Operating Current 135% (A)	Phase Current (A)	OLR (A)	Contactor AC3 (A)	Item Code	Per Unit LP (₹)
5 HP	10.13 A	5.85 A	3.8 A - 6.0 A	20 A	IHSASAH1KA	18225.00
7.5 HP	15.19 A	8.77 A	6 A - 9.3 A	20 A	IHSASAJ1KA	
10 HP ▲	20.25 A	11.69 A	8.9 A - 13.5 A	20 A	IHSASAK1KA	
12.5 HP	25.31 A	14.61 A	13.2 A - 20 A	20 A	IHSASAL1KA	19810.00
15 HP ▲	30.38 A	17.54 A	13.2 A - 20 A	20 A	IHSASAL1KB	20240.00
17.5 HP	35.44 A	20.46 A	17.4 A - 24 A	25 A	IHSASAM1KA	
20 HP ▲	40.50 A	23.38 A	22 A - 30 A	32 A	IHSASAN1KA	23190.00

▲ Stockable Item

For details on technical parameters & non stockable items contact nearest sales office.

POWER GUARD Submersible Controllers (Standard)

Features:

- Water Filled / Oil Filled Submersible motor Configuration
- Digital Smart display for clear identification of current and voltage
- OLP, MCB & contactor combination for better efficiency & performance against product safety
- Applicable for 75 mm / 100 mm borewell Submersible Pump application
- Suitable for wide voltage operation
- High quality rubber gasket to prevent dust entry
- Five-way connector for easy connection



HSN Code: 85369010

Item Code	kW	HP	Type	Descriptions	OLP	MCB	Con-tactor	Run Capacitor μ F (MFD)	Start Capacitor μ F (MFD)	Per Unit LP (₹)
IHQMFDM1F1	0.37 kW	0.5 HP	water Filled	0.5 HP SP STR WATER FILLED R6A	6 A	10 A	20 A	36 μ F	120 μ F - 150 μ F	3585.00
IHRMFDM1F1	0.37 kW	0.5 HP	Oil Filled	0.5 HP SP STR OIL FILLED R6A	6 A	10 A	20 A	36 μ F	-	3350.00
IHQMFDDQ1F1	0.75 kW	1 HP ▲	water Filled	1 HP SP STR WATER FILLED R 10A	10 A	16 A	20 A	50 μ F	120 μ F - 150 μ F	3660.00
IHRMFDDQ1F1	0.75 kW	1 HP	Oil Filled	1 HP SP STR OIL FILLED R10A	10 A	16 A	20 A	36 μ F	-	3545.00
IHSMFDQ1F1	0.75 kW	1 HP	Oil Filled	1 HP SP STR OIL FILLED WC R10A	10 A	16 A	0 A	36 μ F	-	2005.00
IHQMFDR1F1	1.1 kW	1.5 HP ▲	water Filled	1.5 HP SP STR WATER FILLED R 12A	16 A	20 A	25 A	72 μ F	150 μ F - 200 μ F	3960.00
IHRMFDR1F1	1.1 kW	1.5 HP	Oil Filled	1.5 HP SP STR OIL FILLED R12A	16 A	20 A	25 A	50 μ F	-	3755.00
IHSMFDR1F1	1.1 kW	1.5 HP	Oil Filled	1.5 HP SP STR OIL FILLED WC R12A	12 A	20 A	0 A	50 μ F	-	2120.00
IHQMFDT1FA	1.1 kW	1.5 HP	Water Filled	1.5 HP SP STR WATER FILLED R14A	16 A	20 A	25 A	(50+50) μ F	150 μ F - 200 μ F	4045.00
IHQMFDU1F1	1.5 kW	2 HP ▲	Water Filled	2 HP SP STR WATER FILLED R 16A	16 A	20 A	25 A	72 μ F	150 μ F - 200 μ F	4130.00
IHQMFDU1FA	1.5 kW	2 HP	Water Filled	2 HP SP STR WATER FILLED R16A CAP 50+50	16 A	20 A	25 A	(50+50) μ F	150 μ F - 200 μ F	4220.00
IHRMFDU1F1	1.5 kW	2 HP	Oil Filled	2 HP SP STR OIL FILLED R16A	16 A	20 A	25 A	72 μ F	-	3955.00
IHQMFV1F1	2.2 kW	3 HP	water Filled	3 HP SP STR WATER FILLED R 25A	25 A	32 A	32 A	(50+50) μ F	200 μ F - 250 μ F	4765.00

POWER GUARD Submersible Controllers (Deluxe)

Features:

- Inbuilt start run capacitor
- Suitable for wide voltage operation
- High quality rubber gasket to prevent dust entry
- Five-way connector for easy connection
- OLR with Single Phasing Protection



HSN Code: 85369010

HP Rating	kW	Overload Relay (A)	Contactor (A)	Start Capacitor μ F (MFD)	Run Capacitor μ F (MFD)	Item Code	List Price in (₹) Per Unit
0.5 HP	0.37 kW	3.8 A - 6.0 A	20 A	80 μ F - 100 μ F	25 μ F	IHADOAH1F1	5600.00
0.5 HP	0.37 kW	3.8 A - 6.0 A	20 A	80 μ F - 100 μ F	36 μ F	IHADOAJ1FA	
1 HP	0.75 kW	6 A - 9.3 A	20 A	100 μ F - 120 μ F	36 μ F	IHADOAJ1FB	
1 HP ▲	0.75 kW	6 A - 9.3 A	20 A	100 μ F - 120 μ F	50 μ F	IHADOAJ1FC	
1 HP	0.75 kW	6 A - 9.3 A	20 A	120 μ F - 150 μ F	50 μ F	IHADOAJ1FD	6175.00
1.5 HP ▲	1.1 kW	8.9 A - 13.5 A	20 A	120 μ F - 150 μ F	50 μ F	IHADOAK1FA	
1.5 HP ▲	1.1 kW	8.9 A - 13.5 A	20 A	150 μ F - 200 μ F	(36+36) μ F	IHADOAK1FB	
2 HP ▲	1.5 kW	13.2 A - 20 A	20 A	150 μ F - 200 μ F	(36+36) μ F	IHADOAL1FA	
2 HP ▲	1.5 kW	13.2 A - 20 A	20 A	150 μ F - 200 μ F	(50+50) μ F	IHADOAL1FB	6605.00
2 HP ▲	1.5 kW	13.2 A - 20 A	20 A	200 μ F - 250 μ F	(50+36) μ F	IHADOAL1FC	
3 HP ▲	2.2 kW	17.4 A - 24 A	25 A	200 μ F - 250 μ F	(50+50) μ F	IHADOAM1FA	7830.00
3 HP ▲	2.2 kW	17.4 A - 24 A	25 A	200 μ F - 250 μ F	(50+36+36) μ F	IHADOAM1FB	

▲ Stockable Item

For details on technical parameters & non stockable items contact nearest sales office.

Effective from 11th March, 2025

List Price (LP) are in Indian ₹ & as per Standard Terms & Conditions **HAVELLS 77**

urja Contactor 4 Pole (16 A to 40 A)

Features:

- Rugged Contactors with heavy duty Contacts with anti-welding silver alloys
- High Mechanical and Electrical Life
- High Terminal Capacity
- Suitable for Wide voltage Fluctuations including sudden DIP in voltage



HSN Code: 85369010

AC-3 Duty Rating at 415 V, 50 Hz Ie (A)	AC-1 Duty Rating at 415 V, 50 Hz Ith (A)	Power Poles	Type	Item Code	Item Description	Per Unit LP (₹)
20 A	25 A	4	UC1 20 F	IHPBC020100*	20 A 4P Contactor	3000.00
25 A	40 A		UC1 25 F	IHPBC025100*	25 A 4P Contactor	3700.00
32 A	45 A		UC1 32 F	IHPBC032100*	32 A 4P Contactor	4200.00
40 A	63 A		UC1 40 F	IHPBC040100*	40 A 4P Contactor	5500.00

urja Contactor 2 Pole (16 A to 40 A)

Features:

- Rugged Contactors with heavy duty Contacts with anti-welding silver alloys
- High Mechanical and Electrical Life
- High Terminal Capacity
- Suitable for Wide voltage Fluctuations including sudden DIP in voltage



HSN Code: 85369010

AC-3 Duty Rating at 415 V, 50 Hz Ie (A)	AC-1 Duty Rating at 415 V, 50 Hz Ith (A)	Power Poles	Type	Item Code	Item Description	Per Unit LP (₹)
20 A	32 A	2	UC1 20 D	IHPBF020100*	20 A 2P Contactor	1440.00
25 A	40 A		UC1 25 D	IHPBF025100*	25 A 2P Contactor	2050.00
40 A	63 A		UC1 40 D	IHPBF040100*	40 A 2P Contactor	2810.00

*To complete the Cat no. suffix the coil voltage from the coil voltage table

AC Coil for 4 Pole

Code*	F	K
AC Voltage	140 V - 270 V	260 V - 440 V

AC Coil for 2 Pole

Code*	F
AC Voltage	140 V - 270 V



urja Thermal Overload Relay 3 Pole

HSN Code: 85364900

Relay Range (A)	Suitable for	Poles	Type	Item Code	Item Description	Per Unit LP (₹)
1.07 A - 1.7 A	4 Pole Contactors	3	UR1 E	IHAR13CE	3P Thermal O/L Relay A/M	2090.00
1.58 A - 2.5 A			UR1 F	IHAR13CF	3P Thermal O/L Relay A/M	
2.4 A - 3.8 A			UR1 G	IHAR13CG	3P Thermal O/L Relay A/M	
3.8 A - 6.0 A			UR1 H	IHAR13CH	3P Thermal O/L Relay A/M	
6 A - 9.3 A			UR1 J	IHAR13CJ	3P Thermal O/L Relay A/M	
8.9 A - 13.5 A			UR1 K	IHAR13CK	3P Thermal O/L Relay A/M	
13.2 A - 20 A			UR1 L	IHAR13CL	3P Thermal O/L Relay A/M	
17.4 A - 24 A			UR1 M	IHAR13CM	3P Thermal O/L Relay A/M	
22 A - 30 A			UR1 N	IHAR13CN	3P Thermal O/L Relay A/M	

urja Thermal Overload Relay 2 Pole



HSN Code: 85364900

Relay Range (A)	Suitable for	Poles	Type	Item Code	Item Description	Per Unit LP (₹)
3.8 A - 6 A	2 Pole Contactors	2	UR1 H	IHAR12CH	2P Thermal O/L Relay A/M	1020.00
6 A - 9.3 A			UR1 J	IHAR12CJ	2P Thermal O/L Relay A/M	
8.9 A - 13.5 A			UR1 K	IHAR12CK	2P Thermal O/L Relay A/M	
13.2 A - 20 A			UR1 L	IHAR12CL	2P Thermal O/L Relay A/M	1115.00
17.4 A - 24 A			UR1 M	IHAR12CM	2P Thermal O/L Relay A/M	
22 A - 30 A			UR1 N	IHAR12CN	2P Thermal O/L Relay A/M	

▲ Stockable Item

For details on technical parameters & non stockable items contact nearest sales office.

Spare Agri Contactor 2P / 4P

HSN Code: 85389000

Type	Rating	Item Code	Per Unit LP (₹)
Housing 2P		ISCPSPMCX016	345.00
Housing 4P		ISCPSPMCX014	555.00
Carrier Assembly 2P		ISSPEX0447	100.00
Carrier Assembly 4P		ISSPEX0446	145.00
2P Contactor Coil	140 V - 270 V	ISSPEP0008	740.00
4P Contactor Coil	200 V - 400 V	ISSPEP0007	845.00
	415 V (260 V - 440 V)	ISSPEP0009	
	240 V (140 V - 270 V)	ISSPEP0011	
Single Fixed Contact 2P / 4P	20 A	ISSPEX0428	120.00
	25 A	ISSPEX0429	160.00
	32 A	ISSPEX0430	170.00
	40 A	ISSPEX0439	205.00
Single Moving Contact 2P / 4P	20 A	ISSPEX0431	175.00
	25 A	ISSPEX0432	250.00
	32 A	ISSPEX0433	285.00
	40 A	ISSPEX0440	345.00
Contact Kit 2P Contactor	20 A	ISSPEX0441	790.00
	25 A	ISSPEX0442	1110.00
	40 A	ISSPEX0444	1465.00
Contact Kit 4P Contactor	20 A	ISSPEX0434	1435.00
	25 A	ISSPEX0435	2230.00
	32 A	ISSPEX0436	2400.00
	40 A	ISSPEX0445	2390.00



▲ Stockable Item

For details on technical parameters & non stockable items contact nearest sales office.

Effective from 11th March, 2025

 List Price (LP) are in Indian ₹ & as per Standard Terms & Conditions **HAVELLS** 79

DOL Starter - Spares

HSN Code: 85389000

Type	Item Code	Per Unit LP (₹)
NO Switch URJA	ISSPEX0437	170.00
ON / OFF Push Button Assembly URJA	ISSPEX0438	



urja ⚡ Single Phase Sub. Starter - Spares

HSN Code: 85389000

Type		Item Code	Per Unit LP (₹)
PB Red for SPSS with 1NC Element		ISCELXLX0001	250.00
	5+16 Element (1.5-2 HP) 1.12 kW - 1.50 kW	ISCELXLX0002	470.00
	5+25 Element (3-5 HP) 2.24 kW - 3.73 kW	ISCELXLX0003	535.00
Neon Light Indicator Red		ISCELKLX0006	100.00
Front Add-on Aux.Cont.Blk	2NO	ISSPEX0427	530.00
Combined AV Meter	30 A - 300 V	ISCELMLX0006	1405.00
	25 A - 500 V	ISCELMLX0007	1410.00
	50 A - 500 V	ISCELMLX0008	1550.00
Terminal Block	2 Way SPSS	ISCPMPSX032	55.00
	5 Way	ISCELXPX0003	195.00



▲ Stockable Item

For details on technical parameters & non stockable items contact nearest sales office.

Type	Item Code	Per Unit LP (₹)
Start Push Button - Green	ICELL00002	215.00
Stop Push Button - Red	ICELL00003	
Motor ON Indicating Light-Green	ICELKL00015	345.00
Motor Trip Indicating Light-Yellow	ICELKL00013	
SPP	ISCELXL00063	3605.00
Combined Voltmeter & Ammeter	ISCEMLX0007	1410.00
Terminal Block 6 way	ICELPSMX001	530.00
Terminal Block 3 way	ICELPSMX002	320.00
VOLT.SEL SW. C/G	ICELQL00021	495.00
Star Delta Timer	ICELRPSL005	3105.00
Front Block 1NO 1NC	ISPNAFM711	555.00
Mini Rocker Switch - SPP By Pass	ISCELEL00218	55.00



▲ Stockable Item

For details on technical parameters & non stockable items contact nearest sales office.